



## ALRE

### WPR series liquid expansion contact/immersion thermostat

Application: control the temperature of piping and boiler, immersion thermostat with immersion rod and immersion sleeve, temperature set by knob or internal adjustable by screw driver.



WPR-90GA



WPR-90GA-2



WPR-90GB



WPR-90GB-2



WPR-80GB



WPR-90GC



WPR-90GD



WPR-90GE

Model	WPR-90GA	WPR-90GA-2	WPR-90GB	WPR-90GB-2	WPR-80GB	WPR-90GC	WPR-90GD	WPR-90GE
Electrical rating	16(A)250V	16(A)250V	16(A)250V	16(A)250V	16(A)250V	16(A)250V	16(A)250V	16(A)250V
Temperature range	0~90°C	0~90°C	0~90°C	0~90°C	0~80°C	0~90°C	0~90°C	0~90°C
Switching differential	5°C	5°C	6°C±3	6°C±3	5°C±3	4°C±2	9°C	5°C
Temperature sensing part (MAX)	110°C	110°C	110°C	110°C	110°C	110°C	110°C	120°C
Pocket size	φ 8x100mm,ZG1/2"	φ 8x100mm,ZG1/2"						φ 8x100mm,ZG1/2"
Remark		Internal adjust		Manual reset/ Internal adjust	With 1500mm clamping spring	1000mm 1000 mm capillary tube in red PVC	Plastic cover can be white or orange	Plastic cover can be white or orange