

ROTARY MOTORIZED VALVES  
**MIXING VALVE**  
**SERIES 3MG**



External thread/  
Pump flange

3MG, DN 15–32, DZR brass. PN 10. Pump flange connection in combination with external thread.

**VALVE 3MG DESIGNED FOR**

- Heating
- Comfort cooling
- Potable water
- Floor heating
- Solar heating
- Ventilation
- Zone
- District hot water
- District heating
- District cooling

**SUITABLE ACTUATORS**

The valve series 3MG may most easily be fitted with ESBE actuators. See separate pages in beginning of this brochure.

**TECHNICAL DATA\***

Pressure class: \_\_\_\_\_ PN 10  
 Media temperature: \_\_\_\_\_ max. +130°C  
 \_\_\_\_\_ min. -10°C

PED 97/23/EC, article 3.3

N.B.! Maximum 50% glycol for freezing protection and oxygen absorbing compounds are allowed as additives.

\* See product catalogue or visit [esbe.eu](http://esbe.eu) for further detailed information.

**SERIES 3MGP, PUMP FLANGE AND EXTERNAL THREAD**

Art. No.	Reference	DN	Kvs*	Connection	Note	Euro/pcs
1100 55 00	3MGP 15	15	2.5	G 1" / G 1½" / PF 1½"		69,00
1100 56 00	3MGP 20	20	6.3			69,00
1100 20 00	3MGP 25	25	8			69,00
1100 57 00	3MGP 32	32	18	G 1¼" / G 1½" / PF 2"		75,00

\* Kvs-value in m<sup>3</sup>/h at a pressure drop of 1 bar. PF = Pump Flange

**MIXING VALVE**  
**SERIES 5MG**



Internal thread

5MG, DN 25–32, brass, PN 10. Internal thread connection.

**VALVE 5MG DESIGNED FOR**

- Heating
- Comfort cooling
- Potable water
- Floor heating
- Solar heating
- Ventilation
- Zone
- District hot water
- District heating
- District cooling

**SUITABLE ACTUATORS**

The valve series 5MG may most easily be fitted with ESBE actuators. See separate pages in beginning of this brochure.

**TECHNICAL DATA\***

Pressure class: \_\_\_\_\_ PN 10  
 Media temperature: \_\_\_\_\_ max. +130°C  
 \_\_\_\_\_ min. -10°C

PED 97/23/EC, article 3.3

N.B.! Maximum 50% glycol for freezing protection and oxygen absorbing compounds are allowed as additives.

\* See product catalogue or visit [esbe.eu](http://esbe.eu) for further detailed information.

**SERIES 5MG, INTERNAL THREAD**

Art. No.	Reference	DN	Kvs*	Connection	Note	Euro/pcs
1100 52 00	5MG 25	25	8	Rp 1"		112,00
1100 53 00	5MG 32	32	18	Rp 1¼"		136,00

\* Kvs-value in m<sup>3</sup>/h at a pressure drop of 1 bar.