

# ADJUSTABLE ELECTRIC THERMOSTAT type TU SC - TU 10 B - TU RM B

## ADJUSTABLE THERMOSTAT TU SC

(surface contact)

Temperature range 30 -90 C

This thermostat is normally installed to control temperature on pipes of boilers for central heating with diameters from 3/4" to 3". It is supplied with one steel mounting spring to the pipe.



## ADJUSTABLE THERMOSTAT TU 10 B

Temperature range 30 -90 C

This thermostat is normally installed as immersion system (acquastat), on boilers for central heating application.

## MANUAL RESET THERMOSTAT TU RM B

### Typical applications

Boilers for central heating and where is requested a manual reset safety device .

### Temperature setting

They are according to the costumers request.

TEMPERATURE RANGE	MAX WORKING TEMPERATURE ON THE THERMOSTAT	MAX WORKING TEMPERATURE BULB
30° - 90° C		99° C

### SWITCH RATING:

RESISTIVE 10 A 400 V

INDUCTIVE 1 A 400 V

TAB TYPE 1/4" FASTON with screw terminals

ELECTRIC DIAGRAM



NORMAL VERSION **ST** FOR TU RM B



DOUBLE THROUGH VERSION **DT** FOR TU 10 B and TU SC

...

